





Marble 35



Marble 90




Marble 47



Marble 96



Marble 27



Marble 97



Marble 77



Marble 98

<p>CONSTRUCTION Tufting 1/12" loop tip/sheared</p> <p>PILE MATERIAL 100% PA 6 IMPRELE® solution dyed</p> <p>PRIMARY BACKING Non woven PES</p> <p>SECONDARY BACKING TwinBack</p> <p>PILE WEIGHT ISO 8302 Ca. 800 gr/m²</p> <p>TOTAL WEIGHT Ca. 2.400 gr/m²</p> <p>PILE HEIGHT Ca. 3,6 - 5,2 mm</p> <p>TOTAL HEIGHT Ca. 7,7 - 9,3 mm</p> <p>TUFT DENSITY Ca. 282.000/tm²</p> <p>PILE DENSITY Ca. 0.122 g/cm³</p> <p>CLASSIFICATION EN 1307 32 - LC2</p> <p>CASTOR CHAIR SUITABILITY EN 385 A: Intensive use</p> <p>STAIR SUITABILITY EN 1963 A: Intensive use</p>	<p>PERMANENTLY ANTISTATIC ISO 6356 ≤ 2 kV</p> <p>IMPACT NOISE RATING ISO 140-8 26 dB ΔLw</p> <p>SOUND ABSORPTION ISO 354 0,25 αw</p> <p>THERMAL RESISTANCE ISO 8302 0,11 m²·K/W</p> <p>FASTNESS TO LIGHT ISO 105-E02 ≥ 7</p> <p>COLOUR FASTNESS TO WATER EN ISO 105-E01 ≥ 4-5</p> <p>RUBBING FASTNESS EN ISO 105-X12 ≥ 4</p> <p>FIRE RESISTANCE EN 13501-1 Cfl-s1</p> <p>NUMBER OF COLOURS 9</p> <p>WIDTH EN ISO 3018 ca. 400 cm</p>
--	---

